



Neostar

ABC N-Type

Mono-Glass Model

Up to **23.7%**
465W-485W



Product Warranty



Performance
Warranty

Premium Appearance

No grid lines on the front

Higher Power Output

Higher efficiency: 23.7%

Lower degradation: 1 year $\leq 1.0\%$, 2 -30 year $\leq 0.35\%$

Better temperature coefficient: $-0.26\%/^{\circ}\text{C}$

Optimized Balance of System (BOS)

Significant savings on mounting structure, cabling, and labour cost

Shading Unique Optimization

Complete Set of Quality Management System

IEC 61730 (2023) IEC 61215 (2021)

ISO 9001:2015 Quality Management System



ISO 14001:2015 Environmental Management System

ISO 45001:2018 Occupational Safety and Management System

(Made in China)



485W 23.7% ≤1% ≤0.35%
 Output Efficiency First-year Degradation Annual Degradation from Year 2-30



Electrical Characteristics (STC: AM1.5 1000W/m² 25°C NOCT: AM1.5 800W/m² 20°C 1m/s) Power Sorting Tolerance:0~+3%

Model	AIKO-G465-MCH54Mw		AIKO-G470-MCH54Mw		AIKO-G475-MCH54Mw		AIKO-G480-MCH54Mw		AIKO-G485-MCH54Mw	
	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
P _{max} [W]	465	350	470	354	475	358	480	361	485	365
V _{oc} [V]	40.27	38.03	40.37	38.12	40.51	38.26	40.65	38.39	40.79	38.52
V _{mp} [V]	33.38	31.52	33.48	31.61	33.58	31.71	33.68	31.80	33.78	31.90
I _{sc} [A]	14.80	11.97	14.86	12.02	14.93	12.07	15.00	12.13	15.07	12.19
I _{mp} [A]	13.94	11.12	14.05	11.21	14.15	11.29	14.26	11.38	14.37	11.46
Module Efficiency	22.8%		23.0%		23.2%		23.5%		23.7%	

Note: Measurement tolerance for Pmax:±3%

Mechanical Specification

Cell Type	N-Type ABC
Glass	Mono-Glass, 3.2 mm tempered glass
Frame	Anodized aluminum
Cable	4mm ² (IEC) 12AWG(UL) 1200mm or Customized Length
No. of Cells	108(6*18)
Junction Box	IP68, three bypass diodes
Connector	MC4 EVOA/MC4 EVO2
Weight	23kg±3%
Dimension	1802*1134*30mm
Package Detail	36pcs per pallet/216 pcs per 20' GP/864pcs per 40' HQ

Temperature Ratings (STC)

Temperature Coefficient of I _{sc}	+ 0.05%/ °C
Temperature Coefficient of V _{oc}	- 0.22%/ °C
Temperature Coefficient of P _{max}	- 0.26%/ °C

Installation Guide

Operation Temperature	- 40°C~+85°C
Maximum Series Fuse Rating	25A
Protection Class	Class II
V _{oc} and I _{sc} Tolerance	±3%
Maximum System Voltage	DC1500V
Maximum Static Loading	Front 5400Pa Back 2400Pa
Hail Test	25 mm diameter hail at 23 m/s
Fire Rating	IEC Class C



Zhejiang Aiko Solar Technology Co., Ltd.
 www.aikosolar.com
 marketing@aikosolar.com

*AIKO Energy reserves right to update the specification without notice
 DS_EN_2404_V1.3